

MINI-MAX Rotary Meter Mounted Corrector

ORDER FORM & CHECK LIST

PO # _____

DATE _____

BILL TO: _____

SHIP TO: _____

ATTN: _____

ATTN: _____

Use this list to order MINI-MAX Rotary Meter Mounted Correctors

Items 1-6 & 11 are the minimum required specifications

1. <input type="checkbox"/> MINI-MAX Audit Trail Memory <input type="checkbox"/> MINI-MAX -AT 4-items 10-Items <input type="checkbox"/> MINI-MAX -ATX 4-items 10-Items <input type="checkbox"/> PT <input type="checkbox"/> P <input type="checkbox"/> T <input type="checkbox"/> V	QTY: _____
--	-------------------

2. PRESSURE TRANSDUCER:

<input type="checkbox"/> 0 - 1 PSI (0.07 Bar) Gauge only
<input type="checkbox"/> 0 - 3 PSI (0.2 Bar) Gauge only
<input type="checkbox"/> 0 - 6 PSI (0.4 Bar) Gauge only
<input type="checkbox"/> 0 - 15 PSI (1.0 Bar) Gauge only
<input type="checkbox"/> 0 - 30 PSI (2.0 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 60 PSI (4.0 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 100 PSI (7.0 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 150 PSI (10.0 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 200 PSI (14.0 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 300 PSI (20.0 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 600 PSI (41 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 1000 PSI (70 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute
<input type="checkbox"/> 0 - 1500 PSI (100 Bar) <input type="checkbox"/> Gauge <input type="checkbox"/> Absolute

Pressure Units if not PSI: _____

3. TEMPERATURE SYSTEM:

Internal: 3/16" dia x 3" Probe w/ Teflon shielded cable

External: 1/4" dia x 6" Probe w/ Teflon shielded cable

Thermowell, Size; Length: _____ Dia: _____

4. POWER SUPPLY:

4 D-CELL ALKALINE RECEPTACLE p/n 40-2595

4 D-CELL ALKALINE DISPOSABLE p/n 40-2596

5. METER MANUFACTURER and SIZE:

AMCO:	Dresser:	Romet:
RPM <i>pre '06 only</i>	LMMA B3 * Requires Ext. Temp	<input type="checkbox"/> Internal Temp Probe <input type="checkbox"/> External Temp Probe
<input type="checkbox"/> 9C	<input type="checkbox"/> 8C	<input type="checkbox"/> RM1000
<input type="checkbox"/> 1.5M	<input type="checkbox"/> 11C	<input type="checkbox"/> RM1500
<input type="checkbox"/> 3.5M	<input type="checkbox"/> 15C	<input type="checkbox"/> RM2000
<input type="checkbox"/> 5.5M	<input type="checkbox"/> 2M	<input type="checkbox"/> RM3000
<input type="checkbox"/> 7M	<input type="checkbox"/> 3M	<input type="checkbox"/> RM5000
<input type="checkbox"/> 11M	<input type="checkbox"/> 5M	<input type="checkbox"/> RM7000
<input type="checkbox"/> 16M	<input type="checkbox"/> 7M	<input type="checkbox"/> RM11000
<input type="checkbox"/> 23M	<input type="checkbox"/> 11M	<input type="checkbox"/> RM16000
	<input type="checkbox"/> 16M	
	<input type="checkbox"/> 23M*	
	<input type="checkbox"/> 38M*	
	<input type="checkbox"/> 56M*	
	<input type="checkbox"/> 102M*	

6. NUMBER OF VOLUME DIGITS and UNITS:

Digits: 8 7 6 5 4 Units: (MCF, CCF, m3, etc.)

UncVol: _____

CorVol: _____

7. PRESSURE SPECIFICATIONS:

013 BASE PRESSURE: _____

014 ATMOS PRESSURE: _____

LIVE GAS PRESSURE

OR

008 FIXED GAS PRESSURE (FOR -T Only)

Avg. Press (for Super): 0.00 _____

044 PRESSURE FACTOR (Fp): 1.0000 _____

8. TEMPERATURE SPECIFICATIONS:

034 BASE TEMPERATURE: _____

LIVE GAS TEMPERATURE

OR

026 FIXED TEMPERATURE (FOR -P Only)

Avg.Temp (for Super) 60.00 °F _____

9. SUPERCOMPRESSIBILITY: YES NO

053 SPECIFIC GRAVITY: _____

054 MOL %N₂: _____

055 MOL %CO₂: _____

10. DISPLAY LIST ITEMS:

<input type="checkbox"/> Default	<input type="checkbox"/> Custom	
<input type="checkbox"/> CorVol	<input type="checkbox"/> 130 (1,#1)	<input type="checkbox"/> 075 (2,#1)
<input type="checkbox"/> UncVol	<input type="checkbox"/> 131 (1,#2)	<input type="checkbox"/> 076 (2,#2)
<input type="checkbox"/> REI BKup	<input type="checkbox"/> 132 (1,#3)	<input type="checkbox"/> 077 (2,#3)
(PRESS)	<input type="checkbox"/> 133 (1,#4)	<input type="checkbox"/> 078 (2,#4)
TEMP-- °F	<input type="checkbox"/> 134 (1,#5)	<input type="checkbox"/> 079 (2,#5)
DIAL RATE	<input type="checkbox"/> 135 (1,#6)	<input type="checkbox"/> 080 (2,#6)
BAT-VOLT		<input type="checkbox"/> 081 (2,#7)
		<input type="checkbox"/> 082 (2,#8)
		<input type="checkbox"/> 083 (2,#9)
		<input type="checkbox"/> 084 (2,#10)
		<input type="checkbox"/> 085 (2,#11)
		<input type="checkbox"/> 086 (2,#12)

11. ACCESSORIES (OPTIONAL):

MasterLink32 Software

Mi Palm Suite

Mi Pocket PC Suite

* I/O Computer Cable p/n 40-1629

*MPA (Programming Adapter) p/n 40-2620

Configuration/Calibration Cable p/n 40-2696-1

External RS-232 Case Connector p/n 40-2717

Cap Only Shorting Plug Plug & Terminal Strip

Internal Messenger Modem p/n 40-3000

Tii Surge Suppressor Tni Surge Suppressor

Protocol Translator (PT) Board p/n 40-2655

Valve & 1/8" St.St. Tubing Kit p/n 20-5318

Pressure Isolation Union p/n 20-9253

Other: _____

4-20 mA External Station Assembly PJT 02-02-01-1

Print in indicates standard or default configuration



Mercury Instruments, Inc.

3940 Virginia Avenue, Cincinnati, Ohio 45227

(513) 272-1111 FAX# (513) 272-0211 www.mercuryinstruments.com

* Both items are required for Firmware Upgrade